

AMENDMENTS TO THE CLAIMS

Please amend claims 1, 19, 27, 30, and 32, as follow. A complete listing of the claims is provided, as follows.

1. (Currently Amended) A device for managing network traffic flow, the device comprising:
a first processor, the first processor configured to
receive network traffic content,
determine whether a protocol of the network traffic content matches a prescribed
protocol of network traffic content that could contain content desired to be detected by
comparing a type of the network traffic content with a prescribed type, and
store the network traffic content in a stack when the protocol of the network
traffic content matches the prescribed protocol, and
perform filtering of the network traffic if the type of the network traffic content
does not match the prescribed type; and
a second processor associated with the stack, wherein the second processor is configured
to determine whether the network traffic content contains the content desired to be detected if the
type of the network traffic content matches the prescribed type.
2. (Previously Presented) The device of claim 1, wherein the first processor comprises a
general purpose processor.
3. (Previously Presented) The device of claim 1, wherein the first processor comprises an
ASIC processor.
4. (Original) The device of claim 3, wherein the ASIC processor is a semi-custom ASIC
processor.
5. (Original) The device of claim 3, wherein the ASIC processor is a programmable ASIC
processor.

6. (Previously Presented) The device of claim 1, wherein the first processor is further configured to send the network traffic content to a user when the protocol of the network traffic content does not match the prescribed protocol.
7. (Original) The device of claim 1, further comprising the stack.
8. (Previously Presented) The device of claim 7, wherein the stack is implemented in the first processor or in the second processor.
9. (Previously Presented) The device of claim 8, wherein the stack is configured to store the network traffic content in accordance with the protocol of the network traffic content.
10. (Previously Presented) The device of claim 1, wherein the first or the second processor is further configured to assemble the at least a portion of the network traffic content with the rest of the network traffic content, and transmit the network traffic content to a user when it is determined that the network traffic content does not contain the content desired to be detected.
- 11-12. (Canceled)
13. (Previously Presented) The device of claim 1, wherein the second processor comprises an ASIC processor.
14. (Previously Presented) The device of claim 1, wherein the first or the second processor is further configured to flag the network traffic content when the protocol of the network traffic content matches the prescribed protocol, and send the flagged network traffic content to the memory.
- 15-16. (Canceled)

17. (Previously Presented) The device of claim 14, wherein the second processor comprises an ASIC processor.

18. (Original) The device of claim 1, wherein the content desired to be detected is selected from the group consisting of a virus, a worm, a web content, a Trojan agent, an email spam, and a packet transmitted by a hacker.

19. (Currently Amended) A method for managing network traffic flow, the method comprising:

receiving network traffic content at a first processor;

determining whether a protocol of the network traffic content matches with a prescribed protocol of network traffic content that could contain content desired to be detected by comparing a type of the network traffic content with a prescribed type;

performing filtering of the network traffic by the first processor if the type of the network traffic content does not match the prescribed type;

storing the network traffic content in a stack when the protocol of the network traffic content matches the prescribed protocol, the stack associated with a module including a second processor that is configured to determine whether the network traffic content contain content desired to be detected if the type of the network traffic content matches the prescribed type; and

sending at least a portion of the network traffic content to a memory when the protocol of the network traffic content matches the prescribed protocol;

wherein the first and second processors are parts of a device.

20. (Original) The method of claim 19, wherein the network traffic content is stored in the stack in accordance with the protocol of the network traffic content.

21. (Previously Presented) The method of claim 19, further comprising:

assembling the at least a portion of the network traffic content with the rest of the network traffic content, and sending the network traffic content to a user when it is determined that the network traffic content does not contain the content desired to be detected.

22. (Previously Presented) The method of claim 19, further comprising:
flagging the network traffic content when the protocol of the network traffic content matches the prescribed protocol; and
storing the flagged network traffic content in a memory.
- 23-26. (Canceled)
27. (Currently Amended) A device for managing network traffic flow, the device comprising:
a first processor, the first processor configured to
receive network traffic content,
flag the network traffic content by inserting data or modifying a portion of the network traffic content,
send the flagged network traffic content to a module, the module configured to pass unflagged data to a user and prevent flagged data from being sent to the user, and
send a copy of the network traffic content to a second processor, the second processor configured to determine whether the network traffic content contains content desired to be detected; and
the second processor.
28. (Original) The device of claim 27, wherein the first processor is further configured to transmit the network traffic content to a user when it is determined that the network traffic content does not contain the content desired to be detected.
29. (Original) The device of claim 27, wherein the module comprises a memory, a buffer, or at least a portion of a processor.
30. (Currently Amended) A method for managing network traffic flow, the method comprising:
receiving network traffic content at a first processor;

flagging the network traffic content by inserting data or modifying a portion of the network traffic content;

sending the flagged network traffic content to a module, the module configured to pass unflagged data to a user and prevent flagged data from being sent to the user; and

sending a copy of the network traffic content to a second processor, the second processor configured to determine whether the network traffic content contains content desired to be detected;

wherein the first and second processors are parts of a device.

31. (Original) The method of claim 30, further comprising transmitting the network traffic content to a user when it is determined that the network traffic content does not contain the content desired to be detected.

32. (Currently Amended) The device of claim 1, further comprising ~~the~~ a memory coupled to the first processor.

33. (Previously Presented) The device of claim 27, wherein the first processor is configured to pass a portion of the network traffic content downstream before the second processor finishes processing the network traffic content.

34. (Previously Presented) The device of claim 27, wherein the first processor and the second processor are parts of a processor.

35. (Previously Presented) The device of claim 34, wherein the processor comprises an ASIC processor.

36. (Previously Presented) The device of claim 27, wherein the first processor is configured to flag the network traffic content by modifying data associated with the network traffic content or by inserting data to the network traffic content.

37. (Previously Presented) The method of claim 30, wherein a portion of the network traffic content is passed downstream before the processor finishes processing the network traffic content.
38. (Previously Presented) The method of claim 30, wherein the second processor comprises an ASIC processor.
39. (Previously Presented) The method of claim 30, wherein the network traffic content is flagged by modifying data associated with the network traffic content or by inserting data to the network traffic content.
40. (Previously Presented) A device for managing network traffic flow, the device comprising:
 a first processor, the first processor configured to
 receive network traffic content,
 pass a first portion of the network traffic content downstream, and
 pass a second portion of the network traffic content to a stack for allowing the second portion to be scanned for content that is desired to be detected; and
 a second processor that is configured to scan the second portion for the content desired to be detected.
41. (Previously Presented) The device of claim 40, wherein the first or the second processor is further configured to pass the second portion downstream after the second portion is scanned.
42. (Previously Presented) The device of claim 40, wherein the first portion of the network traffic content is not scanned for the content that is desired to be detected.